

CLAIMS

What is claimed is:

- 5
Sub a1
1. An optical sub-assembly for processing an optical signal, the sub-assembly comprising:
 - a working path of the optical network;
 - a first sub-band of the optical signal carried only by the working path;
 - a protect path of the optical network;
 - 10 a second sub-band of the optical signal carried only by the protect path;
 - a first module disposed along the working path for affecting the working path;
 - and
 - a second module disposed along the protect path for affecting the protect path.
 - 15 2. The sub-assembly of claim 1, wherein the first sub-band is one of a C-band and an L-band, and the second sub-band is the other of a C-band and an L-band.
 3. The sub-assembly of claim 1, wherein the first and second modules are comprised of optical amplifiers.
 - 20 4. The sub-assembly of claim 1, wherein the first and second modules are comprised of band pass filters.
 5. The sub-assembly of claim 1, wherein the first and second modules are comprised of channel add devices.
 - 25 6. The sub-assembly of claim 1, wherein the first and second modules are comprised of channel drop devices.
 - 30 7. The sub-assembly of claim 1, wherein the first and second modules are comprised of demultiplexers.

09847091-050101
T0T050" T6024860

8. The sub-assembly of claim 1, wherein the first and second modules are comprised of multiplexers.

5 9. The sub-assembly of claim 1, wherein the first and second modules are comprised of interleavers.

10. The sub-assembly of claim 1, wherein the first and second modules are comprised of attenuators.

10 11. The sub-assembly of claim 1, wherein the first and second modules are comprised of dispersion compensation modules.

12. A method of processing an optical signal in an optical network, comprising the steps of:

15 separating the optical signal into a first sub-band and a second sub-band;
 routing the first sub-band through a first module and routing the second sub-band through a second module of the same type as the first module; and
 recombining the first and second sub-bands.

20 13. The method of claim 12, wherein the separating step comprises the step of routing the optical signal through an L/C splitter.

25 14. The method of claim 12, further comprising the step of assigning the first sub-band to one of a working path and a protect path and assigning the second sub-band to the other of the working path and protect path.

sub
a1 } 15. The method of claim 12, wherein the routing step further comprises amplifying the first sub-band with the first module and amplifying the second sub-band with the second module.

30 16. The method of claim 12, wherein the routing step further comprises filtering the first sub-band with the first module and filtering the second sub-band with the second module.

09847091-050101
TOTSO "T6024860

- 5 17. The method of claim 12, wherein the routing step further comprises adding at least one channel to the first sub-band with the first module and adding at least one channel to the second sub-band with the second module.
18. The method of claim 12, wherein the routing step further comprises dropping at least one channel from the first sub-band with the first module and dropping at least one channel from the second sub-band with the second module.
- 10 19. The method of claim 12, wherein the routing step further comprises demultiplexing the first sub-band with the first module and demultiplexing the second sub-band with the second module.
- 15 20. The method of claim 12, wherein the routing step further comprises multiplexing the first sub-band with the first module and multiplexing the second sub-band with the second module.
- 20 21. The method of claim 12, wherein the routing step further comprises interleaving the first sub-band with the first module and interleaving the second sub-band with the second module.
- 25 22. The method of claim 12, wherein the routing step further comprises attenuating the first sub-band with the first module and attenuating the second sub-band with the second module.
23. The method of claim 12, wherein the routing step further comprises compensating for dispersion of the first sub-band with the first module and compensating for dispersion of the second sub-band with the second module.
- 30 24. An optical amplifier node for amplifying an optical signal, the amplifier node comprising:
a first amplifier for amplifying only signals from a first sub-band of the optical signal, wherein the signals are carried only by a working path; and

TOTO "T6024860

a second amplifier for amplifying only signals from a second sub-band of the optical signal, wherein the signals are carried only by a protect path.

25. The optical amplifier node of claim 24, further comprising a sub-band splitter for
5 splitting the optical signal into at least two sub-bands.

26. The optical amplifier node of claim 25, wherein the sub-band splitter is an L/C splitter.

10 27. The optical amplifier node of claim 24, further comprising a sub-band combiner for combining at least two sub-bands into the optical signal.

28. The optical amplifier node of claim 27, wherein the sub-band combiner is an L/C combiner.

09347091 050101
T0T050" T6024860